



## CFORCE 450S/450L



<b>Dimensioni</b>	Length x Width x Height	S: 2186x1125x1150 mm L: 2386x1125x1205 mm
<b>Interasse</b>	Wheelbase	S: 1260mm L: 1460mm
<b>Altezza minima da terra</b>	Minimum Ground Clearance	250 mm
<b>Diametro di sterzata</b>	Minimum Turning Diameter	S: 5600mm L: 6500mm
<b>Peso a secco</b>	Curb Weight	S: 336 kg L: 350 kg
<b>Capacità di carico</b>	Payload Capacity	240 kg
<b>Capacità serbatoio</b>	Fuel Capacity	17 litre
<b>Capacità di traino</b>	Hitch towing rating	260 kg (T3) 150 kg (L7e)
<b>Capacità di traino</b> <small>(rimorchio frenato)</small>	Hitch towing rating (trailer with brakes)	612 kg
<b>Tipo di motore</b>	Engine Type	Single cylinder, liquid-cooled, 4-stroke, SOHC, 4-valve
<b>Cilindrata</b>	Displacement	400cc
<b>Alimentazione</b>	Fuel Supply	Bosch EFI
<b>Trasmissione</b>	Transmission	CVT
<b>Trazione</b>	Drive	2WD/4WD/Front differential lock
<b>Freni</b>	Brake	Four wheel hydraulic disc+ rear wheel parking
<b>Sospensione ant.</b>	Front Suspension	Double arched A-arm independent suspension
<b>Sospensione post.</b>	Rear suspension	Double A-arm independent suspension
<b>Escursione ant.</b>	Front Suspension Travel	190mm
<b>Escursione post.</b>	Rear Suspension Travel	R: 225mm
<b>Ammortizzatore</b>	Shock Absorber	Spiral spring oil shock absorber
<b>Cerchi</b>	Wheels	Front: 12x6.0 Rear: 12x7.5
<b>Pneumatico ant.</b>	Front tyre	AT24x8.00-12, 25x8.00-12
<b>Pneumatico post.</b>	Rear tyre	AT24x10.00-12, 25x10.00-12
<b>Colori disponibili</b>	Color	Hunter Green, Lava Orange, Polar White, Sky Blue
<b>Omologazione</b>	Homologation	168 as exhibited 167/LOF/CE